

























product	platform lift Premier	cabin lift Prestige	cabin lift Sovereign	definition pictograms
picture				 no pit required  no extra headroom required
use				 platform lift  open cabin  enclosed cabin  hold-to-run control  automatic control  stretchers possible  wheel chair accessible  very suitable as home lift
advantages	no pit, no machine room/cabinet, no extra headroom			 platform lift  open cabin  enclosed cabin  hold-to-run control  automatic control  stretchers possible  wheel chair accessible  very suitable as home lift
	electric drive	electric drive	electric drive	
	shaft always included	cabin instead of platform	cabin with telescopic doors	
	most economic solution	very suitable as home lift	full automatic control	
certification	very fast installation			
machinery directive	2006 / 42 / EC	2006 / 42 / EC	2006 / 42 / EC	
CE certified by	Liftinstituut	Liftinstituut	Liftinstituut	
general specifications				
type of carrier	platform	open cabin	enclosed cabin	
pit depth	50 mm	70 mm	100 mm	
shaft top	2250 mm	2400 mm	2600 mm (2400 optional)	
machine room or cabinet	no	no	no	
shaft	included	optional	by others	
lifting speed	0,15 m/s	0,15 m/s	0,15 m/s	
lifting capacity	400 / 630 / 1000 kg	400 / 630 / 1000 kg	400 / 630 / 1000 kg	
lift controls				
shaft control	automatic	automatic	automatic	
platform / cabin control	hold to run	hold to run	automatic	
door specifications				
shaft doors	semi automatic	semi automatic	telescopic	
cabin doors	no	no	telescopic	
standard door height	2100 mm	2100 mm	2100 mm	
door entries	single / opposite / adjacent	single / opposite / adjacent	single / opposite	
drive system				
type of drive	screw / nut	screw / nut	screw / nut	
motor power	2,2 / 3,0 / 5,5 kW	2,2 / 3,0 / 5,5 kW	2,2 / 3,0 / 5,5 kW	
voltage	230V 1ph or 415V 3ph	230V 1ph or 415V 3ph	230V 1ph or 415V 3ph	
supply / limits				
maximum stops	8	8	8	
maximum lifting height	appr. 15 m	appr. 15 m	appr. 15 m	
minimum dimensions	800 x 1250	800 x 1000	1100 x 1000	
maximum dimensions	1400 x 2400	1100 x 2100	1100 x 2100	